

Technical Specifications

Internally protected Cabinets



Physical

Rack Configuration	Single
Rack Height	20U – 47U
Width (Rack, Excluding A/C)	600mm/800mm
Width (Extension Closet)	N/A
Rack Depth (mm)	600/800/1000
Rack Weight Capacity	600kg

Material

Doors and Housing	2.0mm Mild Steel
Weather Resistant versions	3CR12 or Full SS on request
Anti-Rust	Zinc Phosphate
Paint	Powder Coated
Colour (Standard)	Matt Black Texture or Goose Grey

Conformance

Warranty	1 Year
Standard	ISO 9001:2000, IEC 297 1975, BS 5954:1980

Security

Door Lock	Swinghandle
-----------	-------------

Door Configurations

	Glass
	Solid Steel
	Mounted Fans – IP54 Rear Door

Air Conditioner

Cooling Capacity (50Hz)	750 – 3900W (2500-13 300BTU)
Type	1 Piece (Combined)
Refrigerant	R134a
Airflow	400-1150 m ³ /h

Operating Temperature Limits

External (min/max °C)	-20/+50
Inside Rack (min/max °C)	+25/+45

Weight	25-86kg
--------	---------

Height/Width/Depth

From (mm)	634/308/227
To (mm)	1234/508/382